550,342

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 7 October 2004 (07.10.2004)

PCT

(10) International Publication Number WO 2004/086843 A1

(51) International Patent Classification7:

.

H05K 13/08

(21) International Application Number:

PCT/IB2004/050331

(22) International Filing Date: 25 March 2004 (25.03.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03100814.7

28 March 2003 (28.03.2003) El

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VULLINGS, Henricus, J., L., M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN OOSTERHOUT, Jacobus, J., G., M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). HORIJON, Joseph, L. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


- (74) Agent: DEGUELLE, Wilhelmus, H., G.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: METHOD OF DETERMINING AT LEAST ONE MARKING ELEMENT ON A SUBSTRATE



(57) Abstract: A method of establishing at least one marking element on a substrate (1). By means of design data of the substrate (1) at least a fictitious marking element (5) on the substrate (1) is determined. The fictitious marking element (5) should then be unique for a predefined area of the substrate (1). The fictitious marking element is obtained by selecting at least two transitions (6, 7, 17, 18) of at least one element on the substrate while the transitions (6, 7, 17, 18) enclose an angle to each other.

WO 2004/086843 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.